



Laser Solution Specialists
 145 Third Street P.O. Box L
 Dassel, MN 55325 -0469
 Phone: 320.275.2118
 Fax: 320.275.2993

STOCK HYPOTUBING

GAUGE	NOMINAL OD	ID	WALL
1/2 x 020	0.5	0.46	0.02
5/16 x 028	0.312	0.258	0.027
4 XTW	0.238	0.218	0.01
STW	0.219	0.199	0.01
6 TW	0.203	0.183	0.01
6 X	0.203	0.189	0.007
7 RW	0.18	0.15	0.015
7 TW	0.18	0.16	0.01
7 X	0.18	0.166	0.007
8 RW	0.165	0.135	0.015
8 XX	0.165	0.15	0.0075
8 SP	0.16	0.15	0.005
8.5	0.156	0.136	0.01
9 RW	0.148	0.118	0.015
9 TW	0.148	0.128	0.01
9 XX	0.148	0.135	0.0065
9.5	0.141	0.119	0.011
10 RW	0.134	0.106	0.014
10 TW	0.134	0.114	0.01
10 XXTW	0.134	0.122	0.006
10.5	0.126	0.106	0.01
11 RW	0.12	0.094	0.013
11 TW	0.12	0.1	0.01
11 XX	0.12	0.112	0.004
11.5	0.115	0.095	0.01
12 RW	0.109	0.085	0.012
12 TW	0.109	0.091	0.009
12 X	0.109	0.097	0.006
12 XX	0.109	0.1	0.0045
13 TW	0.095	0.077	0.009
13 X	0.095	0.085	0.005
13 XX	0.095	0.09	0.0025
13.5	0.089	0.071	0.009
14 RW	0.083	0.063	0.01
14 TW	0.083	0.067	0.008
14 XT	0.083	0.072	0.0055
14 XX	0.083	0.077	0.003
14.5	0.078	0.063	0.0075
15 H	0.072	0.05	0.011
15 RW	0.072	0.054	0.009
15 TW	0.072	0.06	0.006
15 X	0.072	0.063	0.0045
15 XX	0.072	0.0645	0.0038
16 RW	0.065	0.047	0.009
16 TW	0.065	0.052	0.006
16 X	0.065	0.058	0.0038
16.5	0.062	0.052	0.005
17 RW	0.058	0.042	0.008
17 TW	0.058	0.047	0.0055
17 SX	0.058	0.05	0.004

GAUGE	NOMINAL OD	ID	WALL
17 XX	0.059	0.054	0.003
17.5	0.056	0.046	0.005
18 RW	0.05	0.033	0.009
18 TW	0.05	0.038	0.006
18 XT	0.05	0.042	0.004
18 XX	0.05	0.045	0.003
18.5	0.046	0.034	0.006
19 RW	0.042	0.027	0.008
19 TW	0.042	0.033	0.005
19 XX	0.042	0.037	0.003
19.5	0.039	0.027	0.006
20 RW	0.0355	0.024	0.006
20 X	0.0355	0.028	0.004
21 RW	0.032	0.02	0.006
21 TW	0.032	0.023	0.005
21 XTW	0.032	0.025	0.004
21 XX	0.032	0.029	0.002
21.5	0.03	0.024	0.003
22 TW	0.028	0.02	0.004
22 X	0.028	0.021	0.003
22 XX	0.028	0.024	0.002
22.5	0.026	0.02	0.003
23 TW	0.025	0.017	0.004
23 XX	0.025	0.02	0.003
23.5	0.023	0.018	0.003
24 TW	0.022	0.014	0.004
24 XX	0.022	0.016	0.003
25 TW	0.02	0.012	0.004
25 XX	0.02	0.016	0.002
26 RW	0.018	0.01	0.004
26 TW	0.018	0.012	0.003
27 TW	0.016	0.01	0.003
27 XTW	0.016	0.012	0.002
28 XTW	0.014	0.011	0.002
29 TW	0.013	0.01	0.002
30 RW	0.012	0.006	0.003
31 TW	0.01	0.007	0.002
31 XTW	0.01	0.007	0.002
32 TW	0.009	0.006	0.002
33 TW	0.008	0.005	0.002

STOCK WIRE

304 SS FULL HARD

0.005
0.006
0.007
0.008
0.009
0.01
0.011
0.012